

PIONEER Auger Drill

MULTI POWER









Pioneer - Auger Drill

DEPTH CAPACITIES: Based on max pullback & a 25% safety factor

4-1/2" Auger 100 ft / 30 m

PRIME MOVER

Standard unit Yanmar 3TNV82A, 4 cylinder, turbo charged diesel engine

Power: 30 HP @ 3000 RPM

ROTATION UNIT

Standard unit	Direct drive motor w/ universal joint
RPM:	0-85 RPM
Torque:	1066 ft/lbs.
Hydraulic motor:	Char-Lynn

MAST BOWL

Maximum opening: 4-1/2"

MAST AND FEED

Feed stroke:	72"
Pullback:	3044 lbs.
Pulldown:	3044 lbs.
Drill angle:	45 to 90 degree

HYDRAULIC SYSTEM

Controls:	Fully hydraulic, no electronics
System pressure:	3000 PSI
Filtration:	10 micron
Components:	Sauer Danfoss, Valvoil, Rexroth & Parker
Heat exchanger:	Air:oil

WEIGHT 8500 LBS

OPTIONS

Tracked carrier

Skid w/ stabilizer cylinders

Trailer package

Core package

DTH package

French/Spanish labels & manual





MULTI POWER PRODUCTS LTD

975 CROWLEY AVENUE KELOWNA BC CANADA V1Y 9R6 P 250.860.6969 F 250.860.3340

MULTIPOWERPRODUCTS.COM

